

Aluminium-Rundstangen

Nach DIN 1725 / 1747 / 1789 bzw.
1799 (EN 573-3 / 754-1,2,3 / 755-1,2,3)

gezogen / gepresst
Herstellungslänge: 3 m / bei AlMgSi0,5: 6 m



Abmessungen mm D	Gewicht ca. kg/m ²	AlCuMgPb	AlCuBiPb	AlMgSi1	AlMgSi0,5	AlZnMgCu1,5
		EN AW- 2007 W.-Nr. 3.1645	EN AW- 2011 W.-Nr. 3.1655	EN AW- 6082 W.-Nr. 3.2315	EN AW- 6060 W.-Nr. 3.3206	EN AW- 7075 W.-Nr. 3.4365
		F 34 - F 37	F 28	F 28 - F 32	F 22	F 51
5,0	0,055	•				
6,0	0,079	•			•	
7,0	0,108	•				
8,0	0,141	•		•	•	
9,0	0,178	•				
10,0	0,220	•	•	•	•	•
11,0	0,266	•				
12,0	0,317	•		•	•	•
13,0	0,372	•				
14,0	0,431	•			•	
15,0	0,495	•	•	•	•	•
16,0	0,563	•		•	•	
17,0	0,636	•				
18,0	0,712	•	•	•	•	
19,0	0,794	•				
20,0	0,880	•	•	•	•	•
21,0	0,970	•				
22,0	1,064	•		•	•	
23,0	1,163	•				
24,0	1,267	•		•		
25,0	1,374	•	•	•	•	•
26,0	1,487	•				
27,0	1,603	•				
28,0	1,724	•		•		•
30,0	1,979	•	•	•	•	•
32,0	2,252	•		•		•
33,0	2,395	•				
34,0	2,542	•				
35,0	2,694	•	•	•	•	•
36,0	2,850	•		•	•	
38,0	3,175	•		•		
40,0	3,518	•	•	•	•	•
42,0	3,879	•				
45,0	4,451	•	•	•	•	•
46,0	4,653	•				
48,0	5,006	•				
50,0	5,498	•	•	•	•	•
52,0	5,946	•				
55,0	6,649	•	•	•	•	
60,0	7,916	•	•	•	•	•
62,0	8,453	•				
65,0	9,287	•	•	•	•	•
70,0	10,770	•	•	•	•	•
75,0	12,360	•		•	•	

• = lieferbare Abmessungen