



# ALUMINIUM-RUNDROHRE




**Dickwandige Rohre**, AlCuMgPb F 38 (Bohr- und Drehqualität), DIN 1725/1746/1795/9107  
in Herstellungslängen von 3 m



AlCuMgPb EN AW- <b>2007 T4</b> W.-Nr. 3.1645	
Abmessungen mm D x S	F 37 -F 38 Gewicht ca. kg/m
10 x 2,5	0,190
28 x 4,0	0,860
40 x 5,0	1,570
40 x 10,0	2,720
42 x 5,0	1,650
45 x 10,0	3,120
50 x 5,0	2,010
50 x 10,0	3,620
50 x 15,0	4,760



AlCuMgPb EN AW- <b>2007 T4</b> W.-Nr. 3.1645	
Abmessungen mm D x S	F 37 -F 38 Gewicht ca. kg/m
60 x 5,0	2,450
60 x 10,0	4,530
60 x 15,0	6,120
65 x 10,0	4,990
70 x 4,0	2,390
70 x 5,0	2,900
70 x 15,0	7,480
80 x 5,0	3,400
80 x 10,0	6,350
80 x 15,0	8,840
80 x 20,0	10,710



AlCuMgPb EN AW- <b>2007 T4</b> W.-Nr. 3.1645	
Abmessungen mm D x S	F 37 -F 38 Gewicht ca. kg/m
90 x 5,0	3,850
90 x 15,0	10,200
100 x 5,0	4,310
100 x 10,0	8,160
100 x 15,0	11,550
100 x 20,0	14,780
150 x 5,0	6,570
150 x 10,0	12,700
160 x 20,0	24,990
180 x 15,0	22,090

Viele weitere Zwischenabmessungen sind auf Anfrage ebenfalls lieferbar. Fragen Sie einfach an!