


ALUMINIUM-VIERKANTROHRE




AlMgSi0,5 F 22, DIN 1725/1748, (EN 573-3/755-1, 2)
 gepresst, warm ausgehärtet, in Herstellungslängen von 6 m



AlMgSi0,5
 EN AW-
6060 T66
 W.-Nr.
 3.3206

Abmessungen mm
 B x L x S F 22
 Gewicht ca. kg/m


10 x 10 x 1,5	0,138
15 x 15 x 2,0	0,302
20 x 20 x 1,5	0,300
20 x 20 x 2,0	0,388
25 x 25 x 2,0	0,496
25 x 25 x 3,0	0,713
30 x 30 x 2,0	0,615
30 x 30 x 3,0	0,880
34 x 34 x 3,0	1,010
35 x 35 x 2,0	0,713
35 x 35 x 3,0	1,037



AlMgSi0,5
 EN AW-
6060 T66
 W.-Nr.
 3.3206

Abmessungen mm
 B x L x S F 22
 Gewicht ca. kg/m

40 x 40 x 1,5	0,624
40 x 40 x 2,0	0,826
40 x 40 x 2,5	1,050
40 x 40 x 3,0	1,199
40 x 40 x 4,0	1,560
45 x 45 x 2,0	0,929
50 x 50 x 2,0	1,037
50 x 50 x 2,5	1,283
50 x 50 x 3,0	1,540
50 x 50 x 4,0	1,987
50 x 50 x 5,0	2,460



AlMgSi0,5
 EN AW-
6060 T66
 W.-Nr.
 3.3206

Abmessungen mm
 B x L x S F 22
 Gewicht ca. kg/m

60 x 60 x 2,0	1,253
60 x 60 x 2,5	1,553
60 x 60 x 3,0	1,847
60 x 60 x 4,0	2,419
70 x 70 x 4,0	2,851
80 x 80 x 4,0	3,283
80 x 80 x 5,0	4,050
90 x 90 x 4,0	3,715
100 x 100 x 3,0	3,143
100 x 100 x 4,0	4,150
100 x 100 x 5,0	5,130
120 x 120 x 5,0	6,210