


Aluminium-Bleche

AlMg1, G 15 (EN 5005 A, H 24/34)

halbhart, G 15, fassadenplan, abkantfähig (EN 485-1-2-4 / 573-3)



Eloxalqualität Standard

AlMg 1
EN AW-
5005 A
W.-Nr.
3.3315

Fertig eloxiert E6/C0, Naturton

AlMg 1
EN AW-
5005 A
W.-Nr.
3.3315

Dicke/Formate mm D x B x L	Gewicht ca. kg/m ²	Eloxalqualität Standard	Fertig eloxiert E6/C0, Naturton
1,0 x 1000 x 2000	5,40	○	●
1,0 x 1250 x 2500	8,44	○	●
1,0 x 1500 x 3000	12,15	○	●
1,5 x 1000 x 2000	8,10	○	●
1,5 x 1250 x 2500	12,66	○	●
1,5 x 1500 x 3000	18,225	○	●
2,0 x 1000 x 2000	10,80	○	●
2,0 x 1250 x 2500	16,88	○	●
2,0 x 1500 x 3000	24,30	○	●
2,5 x 1000 x 2000	13,50	○	●
2,5 x 1250 x 2500	21,10	○	
2,5 x 1500 x 3000	30,375	○	
3,0 x 1000 x 2000	16,20	○	●
3,0 x 1250 x 2500	25,32	○	●
3,0 x 1500 x 3000	36,45	○	●
4,0 x 1000 x 2000	21,60	○	
4,0 x 1250 x 2500	33,75	○	
4,0 x 1500 x 3000	48,60	○	

● = lieferbare Abmessungen ○ = nicht ständig am Lager